

AC18DA(H5Z) 18V 600ml Caulking Gun

Barcode 4966376403592



Toolless piston replacement

Anti-drip function

6 dispensing speed dial settings

Specifications

Type of power	18V
Type of motor	Brushed
Switch Type	Variable Trigger Switch
Dispensing Speed	0-14mm/s
Dispensing speed dial settings	(1) 0.9mm/s (2) 2.5mm/s (3) 4.3mm/s (4) 8.0mm/s (5) 12.0mm/s (6) 14.0mm/s
Maximum dispensing force	3,000N
Holder size	600ml
Stroke	340ml
Anti-drip function	Yes
Toolless Piston Replacement System	Yes
Light	LED White
Weight	3.3kg
Dimensions (L x H x W)	782 x 252 x 82mm
Standard accessories	Hook and safety glasses

Features

The caulking gun is able to be placed upside down while working thanks to the protrusion on the top of the main body and the rack handle to make it easier to unload and load caulking sausages

Toolless piston replacement - The piston can be detached from the plunger rod by unscrewing the piston counter-clockwise and then attached by screwing the piston in a clockwise direction

Anti-drip function - the piston retracts slightly to prevent the remaining sealing material at the end of the nozzle from dripping

Adjusting the operating speed can be done while operating the caulking gun

Compatible with HiKOKI Multi Volt and BSL18 series batteries

Selling Points

Toolless piston replacement

Anti-drip function

Compatible with HiKOKI Multi Volt and BSL18 series batteries

Applications

Filling joints of interior and exterior windows, walls and tiles

Reinforce waterproofing on wet area walls and floors i.e. Kitchens, bathrooms & laundries

Reinforce airtightness on ducting systems

Joining and attaching plate glass and repairing aquariums

