

### C12RSH3(H1Z) 305mm Slide Compound Mitre Saw

Barcode 4966376412822

Freely adjustable blade & LED Shadow light for precise cutting.

One-touch miter lock for quick & easy adjustments.

Durable metal adjustable scale for enhanced accuracy.

Front access for bevel and miter lock – perfect for narrow jobsites.



**BRUSH  
LESS**  
Brushless Motor

#### Specifications

Power supply	AC 240V
Power input	1,520W
Blade Diameter	305mm (12")
Mount Hole Diameter	25.4mm (1")
Bevel Function	Dual Bevel
Mitre Angle	45° (Left)   57° (right)
Cross Cut: 0° (H x W)	107 x 312mm
Bevel Left 45° (H x W)	70 x 312mm
Bevel Right 45° (H x W)	45 x 312mm
Mitre Left 45° + Bevel Left 45°	70 x 220mm
Mitre Left 31° + Bevel Right 45°	45 x 265mm
Mitre Right 45° + Bevel Right 45°	45 x 220mm
Mitre Right 31° + Bevel Left 45°	70 x 265mm
Maximum Mitre Angle	107 x 170mm
No Load Speed	4,000/min.
Positive Stops	Yes
LED Lighting System	Yes
Dimensions (L x W x H)	873 x 916 x 724mm
Weight	25.5kg
Standard Accessories	Dust bag, Vise Assembly, 8mm Hex. bar wrench, Holder, TCT Saw Blade 305mm, Sub table Assembly.

#### Features

##### Precision Cutting Excellence

Enjoy the freedom to achieve precise cuts with a blade that can be easily adjusted to the cutting line, aided by the precision of an LED Shadow light.

##### Effortless Adjustments

Simplify your workflow with the convenience of a one-touch miter lock, allowing you to make quick and efficient adjustments with just a single touch.

##### Robust Metal Adjustable Scale

Elevate your cutting accuracy and ensure long-lasting durability with a metal adjustable scale, providing a sturdy and reliable reference for your measurements.

##### Perfect for Tight Spaces

Tackle narrow jobsites effortlessly as the bevel and miter lock are conveniently located at the front, offering accessibility and ease of use in constrained work environments.

#### Applications

Cutting various types of wood workpieces and plywood. Decoration panels, soft fiberboards, and hard boards. Cutting aluminum sashes.