Product information

September 2019



DH28PEC(H1Z)

Rotary Hammer 28mm SDS Plus Rotary Hammer

Barcode 4966376327676







3-mode action: hammer drilling, drilling only and hammering only

Forward and reverse functionality

Constant speed control to minimise variation in rotation speed and impact rate



Specifications		
Capacity	Masonry	28mm
	Wood	32mm
	Steel	13mm
Input power		900w
No load speed		0 - 950 (min-1)
Full load impact		0 - 4,300 (min-1)
Joules	EPTA-Procedure	3.2j
	Conventional Value	3.4j
Weight		2.99 kg
Length		355mm

Included Accessories

Plastic case Side handle

Depth guage

Selling Points

Highest drilling speed in its class

Lowest vibration in its class

Improved quick release chuck

Compact and lightweight

Features

3-mode action: hammer drilling, drilling only and hammering only

Includes a soft grip side handle to further improve user comfort

Forward and reverse functionality

Constant speed control to minimise variation in rotation speed and impact rate $\,$

Applications

Drilling anchor holes, concrete, tiles, steel or wood

Tightening machine screw, wood screws

Light-duty chiselling of concrete, groove digging and edging



HiKOKI Power Tools Australia reserves the right to change specifications of parts and accessories of HiKOKI power tools without notice. Product images are for display purposes only. Accessories not included unless otherwise stated. Product information should be confirmed at time of purchase. Errors & Omissions excepted.

HiKOKI 6 YEAR WARRANTY More information about our conditions at **www.hikokipowertools.com.au**