

Cordless VB3616DA 36V Brushless Rebar Cutter and Bender



Features

- Reverse rotation mode for precision angle alignment
- Controller to prevent interruption of bending/cutting operation
- 4 angle settings from 45° to 180°
- Brushless DC motor

Specifications

Capacity – Rebar material yield strength..... 460 N/mm² (47kg/mm²) max

Capacity – Max rebar diameter 16mm

No. of possible rebars at a time

– Cutting..... 10mm max 2, 12mm max 1, 16mm max 1

No. of possible rebars at a time

– Bending..... 10mm max 3, 12mm max 2, 16mm max 1

Bending Angle.....0° to 180° (stepless)

No load speed0 to 16 (min⁻¹)

Speed – Cutting.....2.6 sec

Speed – Bending.....3.8 sec

No. of operations per charge – Cutting 170 approx.

No. of operations per charge – Bending ... 310 approx.

Motor Fan Cooled DC Brushless

Switch..... Trigger

Weight 18.9kg

Dimensions (L x W x H) 510 x 230 x 241mm

Standard accessories Battery cover and Hex bar
wrench 4mm

6 YEAR
POWER TOOLS
WARRANTY*

*6 year warranty on
selected products with online
registration. For details visit
www.hikokipowertools.com.au