

UB18DB(H4Z) 18V 2,000lm Cordless Worklight

Barcode 4966376402052

Adjustable brightness between 350 - 2,000lm

IP54 dust-resistance and splashing water

The battery indicator lamp displays the remaining battery power



Specifications

Power	18V	
Globe	LED White	
Brightness adjustment range	350 - 2,000 lm, 30 levels	
Operation time with a fully charged 5.0Ah battery	2,000lm	Approximately 5.5 hours
	350lm	Approximately 32 hours
Battery indicator lamp	Displays the remaining charging state in five stages	
Light angle adjustable range	360° Vertically (18 positions)	
Dimensions L x W x H	163 x 142 x 209 mm	
Weight without a battery	1.2kg	
Tripod screw hole	5/8" UNCw	

Features

Adjustable brightness between 350 - 2,000lm to ensure suitable lighting of the workplace

The battery indicator lamp displays the remaining battery power.

This cordless work light is manufactured to meet the requirements of IP54 (dust-resistance and splashing water) for electrical equipment as per IEC60529

The cordless work light can be adjusted 360° vertically to get the best angle for lighting the workplace

The intergrated hook allows you to hang the work light at the best position for lighting the workplace and swivels out of the way when not in use

Compatible with HiKOKI Multi Volt and BSL18 series batteries

Included Accessories

Hanging hook

Selling Points

Maximum light flux 2,000lm

Dial to adjust the brightness between 350 and 2,000 lm

Remaining battery indicator

Conforming to IP54 (dust-resistance and splashing water)

Hook for hanging the work light

Angle adjustable 360° vertically

Mountable on a tripod

Applications

Lighting the work site to cover the needs of tradies working in unlit or darkened conditions

6 YEAR
POWER TOOLS
WARRANTY*

*6 year warranty on selected products with online registration. For details visit www.hikokipowertools.com.au