

# **WH36DC(H5Z)**

## 36V Brushless 1/4" Impact Driver

Barcode 4966376404490

5 Modes (Max, Bolt, Bolt Single, Soft, Self Drilling)

IP56 dust & water resistance\*

**Triple Hammer for high efficiency** 

Compact and lightweight for easier use





Specifications		
Power	36V	
Motor	Brushless	
Capacity	Small screw*1	4 to 10 mm (5/32" to 3/8")
	Ordinary bolt	5 to 18 mm (3/16" to 23/32")
	High tension bolt	5 to 14 mm (3/16" to 9/16")
	Self drilling screw	3.5 to 6 mm (1/8" to 1/4") in diameter
Tightening torque* <sup>2</sup>	Power mode	215 Nm
	Bolt mode	215 Nm
	Soft mode	76 Nm
No-load speed (with a battery fully charged at 20°C)	Power mode	0 to 3,400 min- <sup>1</sup>
	Bolt mode	0 to 2,900 min-1
	Bolt single mode	0 to 2,900 min- <sup>1</sup>
	Soft mode	0 to 900 min-1
	Self drilling screw mode	0 to 3,700 min-1
Impact rate (with a battery fully charged at 20°C)	Power mode	0 to 4,100 min-1
	Bolt mode	0 to 4,100 min-1
	Bolt single mode	0 to 4,100 min-1
	Soft mode	0 to 2,000 min- <sup>1</sup>
	Self drilling screw mode	0 to 2,200 min- <sup>1</sup>
Drive	6.35 mm (1/4") bit holder	
Type of switch	Variable speed trigger switch with forward/reverse changeover lever (with brake)	
LED light	White LED (Always ON, Light only SW-ON, and Always OFF)	
Weight	1.6 kg	
Dimensions (L x H )	114 x 241 mm	
+1	1 2 1 1	at the second second

 $<sup>^{\</sup>star 1}\!.$  Tapping screws and wood screws 3 mm in diameter are the smallest screws that the Model WH 36DC can tighten.

#### **Features**

Triple Hammer feature which makes three impacts per rotation providing high efficiency and ease to operate

Conforms to IP56 protection class ratings (dust and water resistant\*)

3 LED light provides more visibility in dark and compact areas Easy grip for ease of use

Easy to operate

#### **Included Accessories**

Belt hook

2 x BSL36A18 Li-ion MultiVolt Battery A

UC18YSL3 Rapid Charger with cooling & USB port

## **Selling Points**

High torque impact driver

IP56\* and Triple Hammer features

Compact and lightweight which is perfect for confined areas

## Applications

Tightening and loosening of all types of bolts and nuts, used for securing structural items

\* These products are designed to be resistant to dust and water. However it is not guaranteed that they will not fail. Refer to user manual for recommended use and maintenance procedures. IP56 Rating applies to certain tools only. Batteries and chargers are not IP56 Rated.



<sup>\*2:</sup> When tightening an M16 high-tension bolt (strength grade 10.9) for three seconds with the socket adapter and the hexagon socket (40 mm in overall length) attached.