

KC18DD (HCZ)

18V Brushless 2 Piece Combination Pack

Barcode 4966376402793

1 x DV18DD 18V Brushless Impact Driver Drill

1 x WH18DD 18V Brushless Impact Driver

2 x BSL1820M 18V 2.0Ah Slide Lithium-Ion Battery

1 x UC18YKSL 18V Lithium-Ion Battery Charger



Specifications

Output Voltage	18V DC
Motor	Fan cooled DC brushless motor
2 Speed gearbox	High and low speed
Switches	Variable speed trigger switch, forward and reverse rotation button (with brake)
Switches	2 - 13mm keyless chuck with automatic spindle lock
Driving a machine screw	6mm
Driving a wood screw	6mmØ x 75mm

Drilling Masonary 13mm Drilling Soft Wood 18mm thick 36mm Drilling Mild steel 1.6mm thick 13mm No load speed - low 0 - 440 rpm No load speed - high 0 - 1,700 rpm Maximum impact rate low 6,600 rpm Maximum impact rate high 25.500 rpm Torque - 20 stage clutch 0.6 to 4.0 Nm Maximum torque soft 26 Nm Maximum torque hard 55 Nm

DV18DD 18V Brushless Impact Driver Drill

Dimensions with battery 170 x 238 x 58 mm (L x W x H)

Weight kg with battery 1.3

Dimensions with battery

Weight kg with battery

WH18DD 18V Brushless Impact Driver

TTTTTE TO BI GSTITESS III. P.	act Dilitei
Output Voltage	18V DC
Motor	Fan cooled DC brushless motor
Switches	Variable speed trigger switch, forward and reverse rotation button (with brake)
Driving a machine screw	4 - 8mm
Driving an ordinary bolt	M5 - M14
Driving an high strength bolt	M5 - M12
Tightening torque	140 Nm
Bit drive size	6.35mm (1/4'') shank
No load speed	0 - 3,200 rpm
Impact rate	0 - 4,000 rpm

1.2

134 x 237 x 58 mm (L x W x H)

Specifications

BSL1820M 18V 2.0Ah Slide Lithium-Ion Battery

No memory effect, so the battery does not have to be exhausted, but you can charge it whenever you want

Fully compatible with HiKOKI & Hitachi 18V slide battery products

Volts 18V

Ampere 2.0Ah

Cell technology Lithium (li-ion) cells

Battery mounting Slide

Dimensions 116 x 76 x 49 (L x W x H)

Weight 380 grams

Battery Level Indicator Yes

Approximate charge time 60 minutes (UC18YKSL)

UC18YKSL Slide Lithium-Ion Battery Charger

OC 10 1 K3L 311de Littilum-1011 B	attery Charger
Volts	18V
Power source	AC single phase
Charging system	Constant current and voltage control
Battery mounting	Slide
Dimensions	87 x 175 x 65 mm (L x W x H)
Weight	350 grams
Battery level indicator	Yes

Features

1 x DV18DD 18V Brushless Impact Driver Drill, lightweight, compact & operable in narrow spaces

 $1\,x$ WH18DD 18V Brushless Impact Driver, lightweight, compact & operable in narrow spaces

2 x BSL1820M 18V 2.0Ah Slide Lithium-Ion Battery

1 x UC18YKSL 18V Lithium-Ion Charger

Compatible with HiKOKI Multi Volt and BSL18 series batteries

Selling Points

A high performance 18V Brushless Impact Driver Drill & Impact Driver 2 piece combination pack with batteries and charger

Applications

This combination pack is suitable for general-purpose applications such as;

- Tightening and loosening various screws, bolts and nuts
- Drilling into mild steel, wood, plastic, aluminum, bricks and concrete