

G3613DVE(H4Z) 36V 125mm Grinder with Slide Switch

Barcode 4966376406555

Grip diameter 56mm

Brake system and other safety functions

Detachable dust filter

LED status indicator

Side handle can be mounted in 3 directions



Specifications

Voltage	36V
Motor type	Brushless
Switch type	Slide
Brake Function	Yes
0 Voltage Restart Protection	Yes
Soft Start	Yes
Overload Protection	Yes
Variable Speed Control Dial	Yes, 6 settings
Kick Back Protection System	Yes
Changeable dust filter	Yes
Spindle Lock	Yes
3 Position side handle	Yes
Light LED	Yes
Grinding Wheel Ø	125mm Ø
Grinding Wheel bore Ø	22.23mm Ø
No load speed	3,200 - 10,000rpm
Weight including battery BSL36A18	3.1kg
Dimensions L x W x H	389 x 141 x 133mm
Spindle Lock	Yes
Battery	Compatible with the HiKOKI MultiVolt battery
Included accessories	Side handle, wrench & depressed centre wheel

Features

The high power 1500W motor provides more productive work time

Detachable filter as standard

Side handle can be mounted in 3 directions

Toolless wheel guard

LED status indicator

Safety functions - Brake Function, Kick Back Protection System, Soft Start, 0 Voltage Restart Protection & Overload Protection

Selling Points

High-power 1500W brushless motor

Detachable filter as standard

Toolless wheel guard

Safety functions - Brake Function, Kick Back Protection System, Soft Start, 0 Voltage Restart Protection & Overload Protection

LED status indicator

Side handle can be mounted in 3 directions

Applications

Removal of casting fin and finishing of various types of steel, bronze, and aluminium materials and castings

Grinding of welded sections or sections cut by means of a cutting torch

Cutting of synthetic resins & concrete, slate, stone, brick, marble, and similar materials