

## DH3628DA(H4Z) 36V SDS PLUS Cordless Rotary Hammer

Barcode 4966376405534

High impact energy 3.2 Joules

UVP (User Vibration Protection)

RFC (Reactive Force Control)

LED level for exact drilling work

2 Step Speed Control

Compatible with the HIKOKI MultiVolt battery



### Specifications

Voltage	36V
Motor type	Brushless
Switch type	Variable speed trigger switch
Impact energy	3.2J
Drilling Range Capacity	Concrete drill bit: 3.4 - 28mm
	Concrete core bit: 25 - 50mm
	Steel: 13mm
	Wood: 32mm
Full load impact rate	0 - 4,300bpm
No-load rotation speed	0-950rpm
3 operating modes	Hammer only, drilling only & Hammer / Drilling
Light	LED
UVP (User Vibration Protection)	Yes
Low Vibration Handle	Yes
RFC (Reactive Force Control)	Yes
One-Push Action for Quick Bit Mounting	Yes
Constant Speed Control	Yes
2 Step Speed Control	Yes
Auto Stop Function	Yes
LED level	Yes
Weight including battery (BSL36A18)	3.9kg
Dimensions L x W x H including battery	356 x 91 x 232mm
Battery	Compatible with the HIKOKI MultiVolt battery

### Features

High drilling speed and chiseling performance with impact energy 3.2 Joules

UVP (User Vibration Protection) - Dynamic vibration absorber & Low vibration handle

RFC (Reactive Force Control) to stop the tool jerking excessively

LED level for exact drilling work

2 Step Speed Control to set appropriate speed for the job

Compatible with the HIKOKI MultiVolt battery

### Selling Points

impact energy 3.2 Joules

UVP (User Vibration Protection)

RFC (Reactive Force Control)

LED level for exact drilling work

2 Step Speed Control

Compatible with the HIKOKI MultiVolt battery

### Applications

Drilling holes into concrete, pilot holes for anchors, nylon plugs, and other plugs

Drilling holes into tiles and bricks

Hammering anchors (by using an anchor setter)

Concrete chiselling, chipping, wall chasing & tile removal