

## BSL3640MVT

## HiKOKI T-PWR MULTI VOLT Battery

36V/18V - 4.0/8.0 Ah

- TABLESS CELL TECHNOLOGY
- HIGH POWER AND PERFORMANCE FOR DEMANDING JOBS





## **Specifications**

Voltage	36V/18V
Battery capacity 36V	4.0 Ah
Battery capacity 18V	8.0 Ah
Battery level indicator	$\checkmark$
Battery dimensions (L x W x H)	134 x 83 x 77 mm
Package dimensions (L x W x H)	141 x 90 x 90 mm
Charging time with UC36YSL2	≈ 40 min.
Weight	980 g
Battery level indicator Battery dimensions (L x W x H) Package dimensions (L x W x H) Charging time with UC36YSL2	134 x 83 x 77 mm 141 x 90 x 90 mm ≈ 40 min.

## **Features**

Maximum power output up to 2,160 W: Delivering up to 50% more power<sup>1</sup> to handle heavy-duty applications with ease and efficiency

Longer runtime: Run longer and stay cool even during demanding applications thanks to the tabless cell technology that generates less resistance and less heat

Quick charging: Short charging time of around 40 minutes with the UC36YSL2 charger

One battery for both 36V and 18V tools: Can power a wide range of HiKOKI 36V and 18V. power tools to complete both light and heavy-duty tasks

Increased durability: The impact-resistant design (rubber overmolded base) enhances the durability of the battery

<sup>&</sup>lt;sup>1</sup>Compared to BSL36B18X (1,440 W Output) and BSL36B18 (1,440 W Output) batteries.

<sup>&</sup>lt;sup>2</sup> Standard accessories vary by country or area.