



Powerful and precise 254 mm compound mitre saw with compact sliding function

- Shadow line technology perfectly marks the cutting line without adjustment efforts for high-precision cuts
- Compactly designed sliding function with no space required behind the mitre saw
- Rigid metallic miter scale with nine positive stops for fast and accurate mitre adjustments
- Maximum flexibility thanks to rotating table and inclinable saw head on both sides
- Effective dust extraction via integrated dust collection funnel
- Implemented brake stops the saw blade quickly for high user safety
- Soft start for long service life of motor and drive
- The table can be extended on the right and the left for sawing wide workpieces; right with integrated end stop
- Quick-action clamp for secure fixing of the work piece

Product ID	C10FSB2H1Z
EAN	4966376421275
Rated input power	1450 W
Voltage	220 V
Mains frequency	60 Hz
Blade diameter	254 mm
Bore size	30 mm
No load speed	450
Max. cutting dimension (0°)	92 x 305 mm
Max. cutting dimension (bevel left 45°)	48 x 305 mm
Max. cutting dimension (bevel right 45°)	26 x 305 mm
Max. cutting dimension (miter left 45°bevel left 45°)	48 x 215 mm
Max. cutting dimension (miter right 45°bevel right 45°)	26 x 215 mm
Max. cutting dimension (miter left 31°bevel right 45°)	x
Max. cutting dimension (miter right 31°bevel left 45°)	x
Bevel function	Dual Bevel
Max. bevel angle (left)	47 °
Max. bevel angle (right)	47 °
Max. miter angle (left)	50
Max. miter angle (right)	50
Tool weight	19 kg
Cable length	2 m
Tool length	766 mm
Tool width	477 mm
Tool height	605 mm
Emission sound pressure	103 dB
Emission sound power	90 dB
Emission uncertainty KpA	3 dB
Sliding function	Yes
LED shadow line	Yes
Laser cutting line	Yes
Groove cutting	Yes
Compact sliding system	Yes
Table width extension	Yes
LED light	Yes

Scope of delivery 1

Saw blade(254mm / 40 teeth), Material clamp, Dust bag, Hex key